

## Mini-Max™ Portable Load Pick-up Tool



USMM-001/002

### *No More Lanyards!*

Operational voltage 27 kV maximum.

Continuous current rating 300 Amp maximum.

Can be used on main line conductor size ranging from #6 copper minimum up to 954 ACSR (1.1" diameter) maximum.

Product weight: 7.1 pounds

Product dimension: 20" long x approximately 2.5" diameter.

The Mini-Max™ is a lightweight, compact, portable load pick-up tool. The Mini-Max™ incorporates the revolutionary safety features of the Break-Safe™ line of tools and incorporates them into a device for load pick-up only.

Load pick up is initiated remotely utilizing a hot stick rather than a bulky lanyard or unsafe hand activation. The Mini-Max™ employs the same fail safe locking pin to prevent accidental load-pick as well as a unique gravity catch lock to prevent the operator from breaking load in the energized state.



*USMM-002 with Duckbilled Head*

The Mini-Max™ is offered in a variety of configurations including floating head for gloved work, duckbilled head for stick operation as well as an option for a soft carrying case.

### HOW TO ORDER:

USMM-001	27 kV - 300 AMPS WITH FLOATING HEAD
USMM-001-S	WITH SOFT CARRYING CASE
USMM-002	27 kV - 300 AMPS WITH DUCKBILLED STYLE
USMM-002-S	WITH SOFT CARRYING CASE



[utilityolutionsinc.com](http://utilityolutionsinc.com)

**UTILITY SOLUTIONS**  
 Innovative Products  
 for the 21<sup>st</sup> Century Lineman  
 Phone: 828-323-8914  
 Fax: 828-323-8410